


Unmanaged LCD Ethernet Switches

Fast Ethernet PoE+				Gigabit PoE+			
Model		FGSD-1022VHP	FGSW-1822VHP	FGSW-2622VHP	GSD-1222VHP	GSW-1820VHP	GSW-2620VHP
Product Image							
Hardware	10/100BASE-TX	8	16	24	-	-	-
	10/100/1000BASE-T	2	2	2	10	16	24
	Mini-GBIC/SFP	2 combo	2	2	2	2	2
	Switch Fabric	5.6Gbps	11.2Gbps	12.8Gbps	24Gbps	36Gbps	52Gbps
	MAC Table	4K	4K	4K	8K	8K	8K
	Jumbo Frame	-	-	-	9K	9K	9K
	Memory Buffer	2.75Mb	2.75Mb	2.75Mb	4.1Mb	4.1Mb	4.1Mb
PoE	PoE Standard	802.3at PoE+	802.3at PoE+	802.3at PoE+	802.3at PoE+	802.3at PoE+	802.3at PoE+
	PoE Port	8	16	24	8	16	24
	PoE Budget	120W	300W	300W	120W	300W	300W
Interface	Auto-negotiation	●	●	●	●	●	●
	802.3x Flow Control	●	●	●	●	●	●
	Ethernet Distance Extension	250m via LCD Control button			250m via LCD Control button		
Physical	Dimensions (W x D x H)	280 x 180 x 44 mm	440 x 233 x 44 mm		280 x 180 x 44 mm	440 x 233 x 44 mm	
	Power Supply	100~240V AC, 50/60Hz			100~240V AC, 50/60Hz		
	EMI/Safety	FCC Class A, CE			FCC Class A, CE		
	Material	Metal	Metal	Metal	Metal	Metal	Metal
	Rack mountable	●	●	●	●	●	●

Touch LCD Industrial PoE Router

Flat-type		
Model		WGR-500-4PV
Product Image		
Hardware	LCD	2.4"Color TFT Touch Screen
	10/100/1000BASE-T	5 (4 LAN,1 WAN)
Power	Inputs	Dual 48~56V DC
	Connector	3-pin terminal block, DC socket
Mechanical	Dimensions (W x D x H)	180 x 25 x 140 mm
	Enclosure	IP30 metal
	Mounting	DIN-rail, wall-mountable and magnetic wall mount
Environment	Operating Temperature	-10~60 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)
Regulatory	Emissions	FCC Class A, CE Class A
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)
PoE	PoE Standard	802.3at PoE+
	PoE Port	4
	PoE Budget	120 watts
	PSE Type	End-span
	Power Pin Assignment	1/2(+), 3/6(-)
Protocol	VLAN	IEEE 802.1Q VLAN
Management	Interface	Web
	SNMP	v1, v2c
	System Log	System log and remote Syslog

All-in-One Industrial Router with PoE



11F, No 96, Minquan Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)
Tel: +886-2-2219-9518 Fax: +886-2-2219-9528 E-mail: sales@planet.com.tw
PLANET reserves the right to change specifications without prior notice. All brand names and trademarks are property of their respective owners. © PLANET Technology Corporation DM-LCD0123



Intuitive Touch LCD Network Solution

Optimize Your Network Efficiency with a Simple Touch

Smart Ethernet Switch Solution to SMEs and Large-scale Networks

Need a smarter way of networking and communications management in your network? PLANET provides a full range of LCD Ethernet Switches to fulfill your needs in the SMEs and large-scale networks, such as enterprises, hotels, shopping malls, government buildings, and other public areas.

PLANET LCD Ethernet Switch series is a cutting-edge Plug and Watch Ethernet solution which consists of Color Touch LCD Ethernet Switches and standard LCD Ethernet Switches to provide quick installation, real-time monitoring of data transmission and PoE work status, and immediate troubleshooting through their unique LCD display found on the products' front panel.


- LCD Ethernet Switches
- Touch LCD 802.3bt Ultra PoE Switches
- Touch LCD 802.3at PoE+ Switches
- Touch LCD Flat-type Switches

PLANET Color Touch LCD Ethernet Switches feature excellent Layer 3 static routing, IPv4/IPv6 VLAN routing and IPv4/IPv6 dual stack management for the purpose of having a highly-secure, flexible management and simpler networking application.


Smart and Intuitive LCD Control

Except for the standard Gigabit Ethernet models, PLANET Color Touch LCD PoE Switches are compatible with IEEE 802.3bt Ultra PoE and 802.3at high power PoE standard offering a total 300~600-watt PoE budget. Via the PIN secured LCD touch screen, it features the following special management and status functions:

- System IP address, VLAN and QoS configuration
- PoE management and status
- Port management and status, and SFP information
- Cable diagnostic and remote IP ping
- Reboot, factory default and save configuration
- ONVIF device list and status



PLANET's Color Touch LCD Ethernet Switches also function as Managed ONVIF switches that can automatically detect the ONVIF IP cameras and easily manage ONVIF IP cameras via floor map. Their user-friendly color touch panel enables the PoE PD power consumption management to be more convenient and efficient than ever, thus bringing an intelligent way of monitoring management for the large-scale surveillance networks. They also greatly eliminate the administrators' burden on managing the IP surveillance network when the network scale grows.



Flat-type			
Model	WGS-5225-8UP2SV	WGS-5225-8P2SV	WGS-5225-8T2SV



Hardware	LCD	2.4"Color TFT Touch Screen	2.4"Color TFT Touch Screen	2.4"Color TFT Touch Screen
	10/100/1000BASE-T	8	8	8
	10G BASE-SR/LR	-	-	-
	1000/2500 BASE-X	2	2	2
	Switch Fabric	26Gbps	26Gbps	26Gbps
Layer 3 Features	Throughput	19.35Mpps	19.35Mpps	19.35Mpps
	IP Interface	8 VLAN	8 VLAN	8 VLAN
	Routing Tables	32	32	32
Protocols	Routing Protocols	IPv6/IPv4 Static Routing	IPv6/IPv4 Static Routing	IPv6/IPv4 Static Routing
	VLAN	802.1Q, Q-in-Q, Voice VLAN, Private VLAN		
	Spanning Tree	802.1d/802.1w/802.1s	802.1d/802.1w/802.1s	802.1d/802.1w/802.1s
Management	Multicasting	IPv4 IGMP Snooping, IPv6 MLD Snooping		
	Interface	Web, telnet, SSH, SSL, Touch LCD Screen		
	SNMP	SNMP v1, v2c, v3, trap	SNMP v1, v2c, v3, trap	SNMP v1, v2c, v3, trap
PoE Spec.	SSH/SSL	●/●	●/●	●/●
	PoE Standard	802.3bt PoE++	802.3at PoE+	-
	PSE Type	End-span+Mid-span	End-span	-
	Power Pin Assignment	Pair: 1/2(-), 3/6(+) Pair2: 4/5(+), 7/8(-)	1/2(+), 3/6(-)	-
PoE Ability	PoE Port	8	8	-
	PoE Power Output	48~54V DC, 95W max.	48~56V DC, 36W max.	-
	PoE Budget	720W	240W	-
	PoE Ability PD@15 watts	8	8	-
	PoE Ability PD@30 watts	8	8	-
Intelligent PoE Control	PoE Ability PD@60 watts	8	-	-
	Over Temperature Protection	-	-	-
	PD Alive Check	●	●	-
	PoE Schedule	●	●	-
	Power Limit	●	●	-
	Scheduled Power Recycling	●	●	-
	PoE Classification	●	●	-
ONVIF Management	PoE Event/Threshold Trap	●	●	-
	ONVIF Management	●	●	-
LCD Features		● System Information, Port Status ● Cable Diagnostic, VLAN Status ● Device Ping ● ONVIF device list ● ONVIF device status ● PoE status, ON/OFF	● System Information, Port Status ● Cable Diagnostic, VLAN Status ● Device Ping ● ONVIF device list ● ONVIF device status ● PoE status, ON/OFF	● System Information, Port Status ● Cable Diagnostic, VLAN Status ● Device Ping
Physical	Smart Fan	-	-	-
	Dimensions (W x D x H)	245 x 36 x 140mm	180 x 25 x 140 mm	180 x 25 x 140 mm
	Power Requirement	Dual 48~54V DC	Dual 48~56V DC	12~48V DC or 24V AC
	Operating Temperature	-20~70 degrees C	-20~70 degrees C	-20~70 degrees C
Regulatory	EMI/Safety	FCC Class A, CE	FCC Class A, CE	FCC Class A, CE

Touch LCD Ethernet Switch / Managed LCD Ethernet Switches

802.3bt PoE++				
Model	GS-6320-24UP2T2XV	GS-5220-24UPL4XVR	GS-5220-24T4XV GS-5220-24T4XVR	GS-5220-16T2XV GS-5220-16T2XVR



Hardware	LCD	2.4" Color TFT Touch Screen		2.4" Color TFT Touch Screen	
	10/100/1000BASE-T	24	24	24	16
	10G BASE-SR/LR	2, backward compatible with 1000X & 2500X	4, backward compatible with 1000X	4, backward compatible with 1000X	2, backward compatible with 1000X
	10G BASE-T	2	-	-	-
	Switch Fabric	128Gbps	128Gbps	128Gbps	72Gbps
Layer 3 Features	Throughput	95.23Mpps	95.23Mpps	95.23Mpps	53.57Mpps
	IP Interface	128 VLAN	128 VLAN	128 VLAN	128 VLAN
	Routing Tables	128	128	128	128
Protocols	Routing Protocols	IPv4/IPv6 Static Routing, OSPFv2		IPv4/IPv6 Static Routing, OSPFv2	
	VLAN	802.1Q, Q-in-Q, Voice VLAN, Private VLAN		802.1Q, Q-in-Q, Voice VLAN, Private VLAN	
	Spanning Tree	802.1D, 802.1w, 802.1s		802.1D, 802.1w, 802.1s	
Management	Multicasting	IPv4 IGMP Snooping, IPv6 MLD Snooping		IPv4 IGMP Snooping, IPv6 MLD Snooping	
	Interface	Console, Telnet, HTTP 2.4" Color LCD Touch Screen		Console, Telnet, HTTP 2.4" Color LCD Touch Screen	
	SNMP	SNMP v1, v2c, v3, trap		SNMP v1, v2c, v3, trap	
PoE Spec.	SSH/TLS	●/●	●/●	●/●	●/●
	PoE Standard	802.3bt PoE++ (Ultra PoE), 802.3at PoE+		-	-
	PSE Type	End-span+Mid-span, End-span, Mid-span		-	-
PoE Ability	Power Pin Assignment	Pair 1: 1/2(-), 3/6(+) Pair 2: 4/5(+), 7/8(-)		-	-
	PoE Port	24	24	-	-
	PoE Power Output	52V DC, 95W max.		-	-
	PoE Budget	600W	600W	-	-
	PoE Ability PD@15 watts	24	24	-	-
	PoE Ability PD@30 watts	20	20	-	-
Intelligent PoE Control	PoE Ability PD@60 watts	10	10	-	-
	PoE Ability PD@90 watts	6	6	-	-
	Over Temperature Protection	●	●	-	-
	PD Alive Check	●	●	-	-
	PoE Schedule	●	●	-	-
	Power Limit	●	●	-	-
	Scheduled Power Recycling	●	●	-	-
ONVIF Management	PoE Classification	●	●	-	-
	PoE Event/Threshold Trap	●	●	-	-
ONVIF Management		●	●	-	-
LCD Features		● System Information, Port Status ● Cable Diagnostic, VLAN Status ● Device Ping		● System Information, Port Status ● Cable Diagnostic, VLAN Status ● Device Ping	
Physical	Smart Fan	●	●	●	●
	Dimensions (W x D x H)	440 x 300 x 55 mm, 1.25U height		440 x 300 x 55 mm, 1.25U height	
	Power Requirement	100~240V AC, 50/60Hz 36~60V DC (R model only)		100~240V AC, 50/60Hz 36~60V DC (R model only)	
	Operating Temperature	0~50 degrees C	0~50 degrees C	0~50 degrees C	0~50 degrees C
Regulatory	EMI/Safety	FCC Class A, CE	FCC Class A, CE	FCC Class A, CE	FCC Class A, CE